

MT1 SERIES

LS Tractor



MT122 / MT125
PREMIUM SUB-COMPACT TRACTORS

6-YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS

MT1 SERIES

PREMIUM SUB-COMPACT TRACTORS

RECOMMENDED IMPLEMENTS/ ATTACHMENTS



LOADER:
High Capacity With
An Abundance Of
Standard Features



BACKHOE:
Excellent Capacity,
Smooth And
Consistent Operation
For Added Control



ROTARY CUTTER:
Durable Heavy Steel
Design Providing
Quality And Strength



BOX BLADE:
Features A Heavy
Welded Steel
Design For Use In
Demanding Applications

FEATURES

- 6 Year Warranty*
- 21.5 HP And 24.7 HP Diesel Engine
- 2 Range Hydrostatic Transmission (2 Pedal)
- Electric Engagement Independent PTO
- Completely Flat Operator Platform



Premium Reversible Seat
High-Back Seat With Fold-able Armrest And Retractable Seatbelt Provide Comfort And Security. *Reversible Seat Only On Backhoe Models



2 Range Hydrostatic Transmission
(2 Pedal) Comfortable And Efficient Operator Control



High Capacity Loader
2 Large Diameter Lift And 2 Large Diameter Curl Cylinders Enable 1,007 lbs. Lift Capacity



Standard Factory Grille Guard W/ Loader
Full Length Grille Guard Protects Body Panels And Radiator



Durability And Capacity
Heavy-Duty Frame And Lift Cylinders Enable 970 lbs. Of Three-Point Lift Capacity



60 Inch Mower Deck
Heavy-Duty Mower Deck Provides An Excellent Cut And Makes Use Of The Standard Mid-PTO



Flat Platform With Rubber Surface
Provides Comfort During Long Hours



Standard Foldable ROPS
Enables Easy Adjustment For Clearance



Color Coded Controls
Enables Inexperienced Operators More Confidence

MT122 / MT125



SPECIFICATIONS

CATEGORY		
ENGINE	MT122	MT125
Type	3 Cylinder, Indirect Injection, Water-cooled	
Model (Tier 4)	Yanmar 3TNV76F	Yanmar 3TNV80F
Engine HP (gross)	21.5	24.7
PTO (HP)	15.0	17.2
Rated Speed (rpm)	3,000	
Displacement (in ³ .)	68.0	77.3
Fuel Tank Capacity (gal.)	6.6	
Alternator (V-A)	12V - 40 AMPS	
DRIVE TRAIN		
Transmission	Hydrostatic Drive	
No. Of Speed	2 Ranges	
Brakes	Wet, Multi-disc	
PTO		
Type	Independent	
Rear (rpm)	Standard (540 rpm)	
Mid (rpm)	Standard (2,500 rpm)	
HYDRAULIC SYSTEM		
Lift Control System	Position	
Implement Pump (gpm)	4.6	
Steering Pump (gpm)	2.1	
Steering	Hydrostatic Power Steering	
Total Flow (gpm)	6.7	
Category (3pt Hitch)	CAT I	
Hitch Lift Capacity (lbs.) (Hitch End)	970 (At 610mm: 728)	
DIMENSION		
Overall Length (Bumper To Link in.)	97	
Overall Width With Tires (in.)	47	
Wheelbase (in.)	56	
Height To Top Of ROPS (in.)	87	
TIRE SIZE		
Front / Rear Industrial	18 x 8.5 - 10 / 26 x 12.0 - 12	
Front / Rear Turf	18 x 8.5 - 10 / 26 x 12.0 - 12	
WEIGHT		
Total Weight w/o Ballast (lbs.)	1,433	1,444

**All Specs and features are subject to change, and pictures could include optional equipment etc.*

FRONT END LOADER		LL1101
TRACTOR APPLICATION		MT1 SERIES
Maximum Lift Height (At Pivot Pin) (in.)		72.0
Clearance With Attachment Dump (in.)		50.0
Reach At Maximum Height (in.)		26.5
Maximum Dump Angle (deg.)		45
Maximum Rollback Angle (deg.)		28
Digging Depth (in.)		4.7
Overall Height In Carry Position (in.)		41.5
Lift Capacity (At Pivot Pin) (lbs.)		1,007
Breakout Force (At Pivot Pin) (lbs.)		1,960
Approx. Weight (Loader w/o Bucket) (lbs.)		300

BACKHOE		LB1107
TRACTOR APPLICATION		MT1 SERIES
Digging Depth (in.)		77.8
Reach From Centerline Of Swing Pivot (in.)		144.9
Loading Height (in.)		59.6
Swing Arc (deg.)		140.0
Transport Height (in.)		74.7
Bucket Rotating (deg.)		169.4
Stabilizer Spread (Down Position) (in.)		78.6
Stabilizer Spread (Up Position) (in.)		53.2
Bucket Digging Force (lbs.)		2,097
Shipping Weight (lbs.)		873

MID-MOUNT MOWER		LM1160
TRACTOR APPLICATION		MT1 SERIES
Cutting Width (in.)		60.0
Overall Width (in.)		75.6
Cutting Height Range (in.)		1 - 4
Deck Shell Thickness (in.)		0.126
Spindle Speed At 3,000 (rpm)		2,786
Blade Tip Speed (ft./min)		14,932
Number Of Blades		3
Blade Length (in.)		20.5
Blade Width (in.)		2.48
Blade Thickness (in.)		0.236
Shipping Weight Of Base 60" Deck (lbs.)		284.4

Additional Equipment

- Standard Factory Toolbox
- Standard 12 Volt Power Outlet
- Mounting Points On ROPS
- Field Cabs Available



LSTractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC