

LS Tractor MT225S COMPARISON



MAKE MODEL	LS TRACTOR MT225s	JOHN DEERE 2025R (2017-Present)	KUBOTA LX2610 / LX2610SU (2020-Present)	MAHINDRA MAX 25XL HST (2019-Present)
ENGINE PERFORMANCE				
Advertised Engine Power, Rated, hp (kW)	24.7	23.9 (17.8)	24.8 (18.5)	24 (17.9)
Fuel Tank capacity, gal (L)	6.79	6.3 (23.8)	7.1 (27) w/ROPS; 8.3 (31.5) w/cab	6.1 (23)
PTO PERFORMANCE				
PTO Horsepower, Basic / Optional Transmission, hp (kW)	19.3	18 (13.4)	19.5 (14.5)	20 (14.9)
PTO Speeds, rpm	540	540	540	540
BASIC ENGINE				
Engine Make	Yanmar	Yanmar	Kubota	Mitsubishi
Displacement, cu in (L)	77.3	77.3 (1.267)	77 (1.261)	80.4 (1.318)
BASIC TRANSMISSION CONFIGURATION				
Transmission Type	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Number of Forward / Reverse Speeds	Infinite, 3 Ranges	Infinite, 2 ranges	Infinite, 3 ranges	Infinite, 2 ranges
Creeper Range Available	np	No	np	np
OPTIONAL TRANSMISSION 1				
Transmission Type	No Option	No option	No option	No option
Number of Forward / Reverse Speeds	No Option	No option	No option	No option
HYDRAULIC SYSTEM				
Implement Pump Flow, gpm (Lpm)	5.6 (21.19)	3.5 (13.25)	8.7 (33.1) total	4.6 (17.5)
Number of Standard Remote Valves	2 mid-location	2 mid-location	Single rear	np
3-POINT HITCH FEATURES				
3-Point Hitch Category	Category 1	Limited Category 1	Category 1	Category 1
3-POINT HITCH LIFT CAPACITY				
Standard Lift Capacity 24 Inches behind pin, lb (kg)		882 (400)	1,676 (760)	np
Standard Lift Capacity at lift pin, lb (kg)		1,234 (560)	2,139 (970)	1,354 (614)
Standard Lift Capacity at hitch end, lb (kg)	1,896 (860)			
Wheelbase / Trackbase				
Wheelbase/Trackbase, MFD/4WD or Track, in (mm)	63.4 (1610)	63 (1600)	65.6 (1666)	58.2 (1480)
Weight (w/Tires or Tracks)				
Weight, MFD/4WD w/ROPS, lb (kg)	1,764 (800)	1,793 (813)	1,786 (810)	1,715 (778)
Weight, MFD/4WD or Tracks w/Cab, without ballast, lb (kg)	No cab	No cab	2,293 (1040)	No cab
Tire / Track Size				
Front Tire Size or Track Width, MFD/4WD or Track	7-12 Ag or 23x8.5-12 R4, or 22x8.5-12 Turf	23x8.5-12, 4PR R3 Turf	7-12, R1 or 23x8.50-14, R4	6x12 Ag or 20x8-10 Industrial
Rear Tire Size or Track Width	11.2-16 Ag, of 12-16.5 R4, or 31x15.5-15 Turf	31x13.5-15, 4PR R3 Turf	12.4-16, R1 or R4	9.5x16 Ag or 27x12.5-15 Industrial